



MACHINING CONDITIONS

CNMM 120408 NR LT 10

T0000669

Material Group	Lamina Group	Material Example	Hardness	D.O.C		Feed		Amax		Vc		Advised D.O.C	Advised Feed [mm/t]	Advised Vc [m/min]
				min[mm]	max[mm]	min[mm/t]	max [mm/t]	[mm^2]	min [m/min]	max [m/min]	[mm]			
Steel	Non Alloyed	C35, Ck45, 1020, 1045, 1060, 28Mn6	125 HB	0.5	7	0.21	0.6	2.88	180	330	4.2	0.46	240	
			190 HB	0.5	7	0.21	0.6	2.88	180	280	4.2	0.42	220	
			250 HB	0.5	7	0.21	0.54	2.4	180	250	4.2	0.4	200	
Steel	Low Alloyed	42CrMo4, St50, Ck60, 4140, 4340, 100Cr6	230 HB	0.5	5.6	0.21	0.54	1.92	120	250	4.2	0.38	180	
			280 HB	0.5	5.6	0.18	0.48	1.92	120	210	4.2	0.36	150	
			180 HB	0.5	7	0.21	0.54	1.92	120	280	4.2	0.38	200	
			350 HB	0.5	4.9	0.18	0.48	1.6	120	180	3.8	0.36	130	
Stainless Steel	High Alloyed	X40CrMoV5, H13, M42, D3, S6-5-2, 12Ni19	220 HB	0.5	5.6	0.18	0.48	1.92	70	190	3.5	0.36	140	
			280 HB	0.5	5.6	0.18	0.48	1.92	70	150	3.5	0.36	120	
			320 HB	0.5	4.2	0.18	0.42	1.28	70	130	3.1	0.34	100	
			350 HB	0.5	4.2	0.18	0.42	1.28	70	110	3.1	0.34	90	
Stainless Steel	Austentic	304, 316, X5CrNi18-9	180 HB	0.5	7	0.2	0.48	1.92	170	270	4.2	0.3	190	
	Duplex		240 HB	0.5	7	0.2	0.48	1.6	160	220	4.2	0.26	170	
Cast Iron	Grey	GG20, GG40, EN-GJL-250, N030B	290 HB	0.5	5.6	0.18	0.42	1.28	80	150	3.5	0.29	100	
			310 HB	0.5	5.6	0.18	0.42	1.28	70	140	3.5	0.29	90	
			200 HB	0.5	7	0.18	0.48	1.12	170	250	3.5	0.24	190	
			42 HRc	0.5	5.6	0.18	0.48	1.12	120	190	3.1	0.24	130	
Cast Iron	Malleable & Nodular	GGG40, GGG70, 50005	150 HB	0.5	7	0.15	0.72	3.2	170	250	4.2	0.42	200	
			200 HB	0.5	7	0.15	0.72	2.88	160	230	4.2	0.42	180	
			250 HB	0.5	7	0.15	0.66	2.88	150	210	4.2	0.42	160	
Niti Alloy	Fe, Ni & Co Based	Incoloy 800, Inconel 700, Stellite 21	150 HB	0.5	7	0.15	0.6	2.4	120	250	4.2	0.36	180	
			200 HB	0.5	7	0.15	0.6	2.08	120	230	4.2	0.36	160	
			250 HB	0.5	7	0.15	0.6	1.92	120	190	4.2	0.36	140	
Niti Alloy	Ti Based	T40, TiAl6V4	T40	-	0.5	4.2	0.2	0.42	1.12	40	60	2.8	0.36	45
			TiAl6V4	-	0.5	4.9	0.2	0.48	1.28	50	70	2.8	0.4	55
Hardened Materials	Steel Chilled Cast Iron White Cast Iron	G-X300CrMo15, X100CrMo13, 440C, G-X260NiCr42	55 HRc	0.5	2.1	0.11	0.24	0.48	30	50	1.4	0.18	40	
			400 HB	0.5	2.8	0.11	0.3	0.64	40	60	2.1	0.22	50	
			45 HRc	0.5	3.5	0.11	0.36	0.96	50	100	2.8	0.3	80	
			50 HRc	0.5	2.8	0.11	0.3	0.64	40	90	2.1	0.24	70	
			55 HRc	0.5	2.1	0.11	0.24	0.48	40	80	1.4	0.22	60	
Aluminium	Al (>8%Si)	AISI12	130 HB	0.5	8.4	0.2	0.72	2.88	200	400	4.2	0.48	280	

