



# MACHINING CONDITIONS

ODMT 060508 TN LT 30

M0001104

Material Group	Lamina Group	Material Example	Hardness	D.O.C		Feed		Vc		Advised D.O.C [mm]	Advised Feed [mm/t]	Advised Vc [m/min]	
				min[mm]	max[mm]	min[mm/t]	max [mm/t]	min [m/min]	max [m/min]				
Steel	Non Alloyed	C35, Ck45, 1020, 1045, 1060, 28Mn6	125 HB	0.5	4	0.22	0.54	190	330	2.5	0.39	250	
			190 HB	0.5	4	0.22	0.54	190	300	2.5	0.39	220	
			250 HB	0.5	4	0.22	0.54	190	250	2.5	0.39	200	
Steel	Low Alloyed	42CrMo4, St50, Ck60, 4140, 4340, 100Cr6	230 HB	0.5	4	0.18	0.43	150	210	2.5	0.34	180	
			280 HB	0.5	4	0.18	0.37	130	190	2.5	0.31	150	
			180 HB	0.5	4	0.18	0.43	150	240	2.5	0.34	200	
			350 HB	0.5	4	0.18	0.37	130	170	2.5	0.31	140	
Steel	High Alloyed	X40CrMoV5, H13, M42, D3, S6-5-2, 12Ni19	220 HB	0.5	2.9	0.14	0.37	90	150	1.9	0.31	130	
			280 HB	0.5	2.9	0.14	0.37	90	130	1.9	0.31	120	
			320 HB	0.5	2.9	0.14	0.31	60	110	1.9	0.27	100	
			350 HB	0.5	2.9	0.14	0.31	60	90	1.9	0.27	80	
Stainless Steel	Austentic	304, 316, X5CrNi18-9	180 HB	0.5	4	0.18	0.37	190	250	2.5	0.31	220	
	Duplex		240 HB	0.5	4	0.14	0.34	160	210	2.5	0.31	190	
Cast Iron	Grey	GG20, GG40, EN-GJL-250, N030B	290 HB	0.5	2.9	0.14	0.31	70	130	1.9	0.27	100	
			310 HB	0.5	2.9	0.14	0.31	70	120	1.9	0.27	90	
			200 HB	0.5	4	0.18	0.37	150	210	2.5	0.31	190	
			42 HRc	0.5	2.9	0.18	0.34	90	150	1.9	0.27	130	
Cast Iron	Malleable & Nodular	GGG40, GGG70, 50005	150 HB	0.5	4	0.22	0.54	150	240	2.5	0.39	200	
			200 HB	0.5	4	0.22	0.54	150	220	2.5	0.39	180	
			250 HB	0.5	4	0.22	0.54	150	190	2.5	0.39	160	
Niti Alloy	Fe, Ni & Co Based	Incoloy 800, Inconel 700, Stellite 21	150 HB	0.5	4	0.18	0.48	100	200	2.5	0.34	180	
			200 HB	0.5	4	0.18	0.48	100	180	2.5	0.34	150	
			250 HB	0.5	4	0.18	0.48	100	150	2.5	0.34	130	
Niti Alloy	Ti Based	T40, TiAl6V4	T40	-	0.5	2.9	0.14	0.31	30	60	1.9	0.27	40
			TiAl6V4	-	0.5	2.9	0.14	0.34	40	70	1.9	0.31	55
Hardened Materials	Steel Chilled Cast Iron White Cast Iron	G-X300CrMo15, X100CrMo13, 440C, G-X260NiCr42	55 HRc	0.4	0.9	0.12	0.24	30	60	0.6	0.2	40	
			400 HB	0.4	1.1	0.12	0.31	40	80	0.9	0.24	50	
			45 HRc	0.4	1.4	0.12	0.31	40	80	1.3	0.24	60	
			50 HRc	0.4	1.1	0.12	0.27	40	70	0.9	0.22	55	
			55 HRc	0.4	0.9	0.12	0.24	40	60	0.6	0.2	50	
Aluminium	Al (>8%Si)	AISI12	130 HB	0.5	4	0.22	0.54	200	400	2.5	0.43	280	