



MACHINING CONDITIONS

ODMW 060508 TN LT 30

M0000451

Material Group	Lamina Group	Material Example	Hardness	D.O.C		Feed		Vc		Advised D.O.C [mm]	Advised Feed [mm/t]	Advised Vc [m/min]
				min[mm]	max[mm]	min[mm/t]	max [mm/t]	min [m/min]	max [m/min]			
Non Alloyed	1	C35, Ck45, 1020, 1045, 1060, 28Mn6	125 HB	0.5	4	0.22	0.58	190	330	3	0.41	250
			190 HB	0.5	4	0.22	0.58	190	300	3	0.41	220
			250 HB	0.5	4	0.22	0.58	190	250	3	0.41	200
Steel	Low Alloyed	42CrMo4, St50, Ck60, 4140, 4340, 100Cr6	230 HB	0.5	4	0.18	0.45	150	210	3	0.36	180
			280 HB	0.5	4	0.18	0.4	130	190	3	0.32	150
			180 HB	0.5	4	0.18	0.45	150	240	3	0.36	200
			350 HB	0.5	4	0.18	0.4	130	170	3	0.32	140
High Alloyed	3	X40CrMoV5, H13, M42, D3, S6-5-2, 12Ni19	220 HB	0.5	2.8	0.14	0.4	90	150	2.3	0.32	130
			280 HB	0.5	2.8	0.14	0.4	90	130	2.3	0.32	120
			320 HB	0.5	2.8	0.14	0.32	60	110	2.3	0.29	100
			350 HB	0.5	2.8	0.14	0.32	60	90	2.3	0.29	80
Cast Iron	Grey	GG20, GG40, EN-GJL-250, N030B	150 HB	0.5	4	0.22	0.58	150	240	3	0.41	200
			200 HB	0.5	4	0.22	0.58	150	220	3	0.41	180
			250 HB	0.5	4	0.22	0.58	150	190	3	0.41	160
Malleable & Nodular	8	GGG40, GGG70, 50005	150 HB	0.5	4	0.18	0.5	100	200	3	0.36	180
			200 HB	0.5	4	0.18	0.5	100	180	3	0.36	150
			250 HB	0.5	4	0.18	0.5	100	150	3	0.36	130
Hardened Materials	11	G-X300CrMo15	55 HRc	0.4	0.9	0.12	0.25	30	60	0.7	0.22	40
			Ni-Hard 2	400 HB	0.4	1.1	0.12	0.32	40	80	0.9	0.25
		X100CrMo13, 440C, G-X260NiCr42	45 HRc	0.4	1.4	0.12	0.32	40	80	1.1	0.25	60
			50 HRc	0.4	1.1	0.12	0.29	40	70	0.9	0.23	55
			55 HRc	0.4	0.9	0.12	0.25	40	60	0.7	0.22	50