



MACHINING CONDITIONS

TCMT 16T312 NN LT 1000

T0001929

Material Group	Lamina Group	Material Example	Hardness	D.O.C		Feed		Amax		Vc		Advised D.O.C	Advised Feed [mm/t]	Advised Vc [m/min]
				min[mm]	max[mm]	min[mm/t]	max [mm^2/t]	[mm^2]	min [m/min]	max [m/min]	[mm]			
Steel	Non Alloyed	C35, Ck45, 1020, 1045, 1060, 28Mn6	125 HB	0.5	5	0.21	0.48	1.94	180	330	3	0.41	240	
			190 HB	0.5	5	0.21	0.48	1.94	180	280	3	0.38	220	
			250 HB	0.5	5	0.21	0.43	1.62	180	250	3	0.36	200	
Stainless Steel	Low Alloyed	42CrMo4, St50, Ck60, 4140, 4340, 100Cr6	230 HB	0.5	4	0.21	0.43	1.3	120	250	3	0.35	180	
			280 HB	0.5	4	0.18	0.38	1.3	120	210	3	0.32	150	
			180 HB	0.5	5	0.21	0.43	1.3	120	280	3	0.35	200	
			350 HB	0.5	3.5	0.18	0.38	1.08	120	180	2.7	0.32	130	
Cast Iron	High Aligned	X40CrMoV5, H13, M42, D3, S6-5-2, 12Ni19	220 HB	0.5	4	0.18	0.38	1.3	70	190	2.5	0.32	140	
			280 HB	0.5	4	0.18	0.38	1.3	70	150	2.5	0.32	120	
			320 HB	0.5	3	0.18	0.33	0.86	70	130	2.2	0.3	100	
			350 HB	0.5	3	0.18	0.33	0.86	70	110	2.2	0.3	90	
Niti Alloy	Austentic	304, 316, X5CrNi18-9	180 HB	0.5	5	0.2	0.38	1.3	170	270	3	0.27	190	
	Duplex		240 HB	0.5	5	0.2	0.38	1.08	160	220	3	0.24	170	
Aluminium	Ferritic & Martensitic	410, X6Cr17, 17-4 PH, 430	290 HB	0.5	4	0.18	0.33	0.86	80	150	2.5	0.26	100	
	Grey		310 HB	0.5	4	0.18	0.33	0.86	70	140	2.5	0.26	90	
Hardened Materials	Malleable & Nodular	GG20, GG40, EN-GJL-250, N030B	200 HB	0.5	5	0.18	0.38	0.76	170	250	2.5	0.22	190	
			240 HB	0.5	4	0.18	0.38	0.76	120	190	2.2	0.22	130	
			150 HB	0.5	5	0.15	0.57	2.16	170	250	3	0.38	200	
Al	Fe, Ni & Co Based	Incoloy 800	200 HB	0.5	5	0.15	0.57	1.94	160	230	3	0.38	180	
			250 HB	0.5	5	0.15	0.52	1.94	150	210	3	0.38	160	
Al	Ti Based	T40	150 HB	0.5	5	0.15	0.48	1.62	120	250	3	0.32	180	
			200 HB	0.5	5	0.15	0.48	1.4	120	230	3	0.32	160	
Al	Steel Chilled Cast Iron White Cast Iron	G-X300CrMo15, X100CrMo13, 440C, G-X260NiCr42	250 HB	0.5	5	0.15	0.48	1.3	120	190	3	0.32	140	
			350 HB	0.5	3	0.2	0.33	0.76	30	40	2	0.3	30	
			240 HB	0.5	3	0.2	0.33	0.76	40	60	2	0.32	45	
			400 HB	0.5	2	0.11	0.24	0.43	40	60	1.5	0.19	50	
			45 HRC	0.5	2.5	0.11	0.29	0.65	50	100	2	0.27	80	
Al	AI (>8%Si)	AISI12	50 HRC	0.5	2	0.11	0.24	0.43	40	90	1.5	0.22	70	
			55 HRC	0.5	1.5	0.11	0.19	0.32	40	80	1	0.19	60	
			130 HB	0.5	6	0.2	0.57	1.94	200	400	3	0.43	280	

