



# MACHINING CONDITIONS

WNMG 080404 NN LT  
1000

T0001951

Material Group	Lamina Group	Material Example	Hardness	D.O.C		Feed		Amax [mm^2]	Vc		Advised D.O.C [mm]	Advised Feed [mm/t]	Advised Vc [m/min]
				min[mm]	max[mm]	min[mm/t]	max [mm/t]		min [m/min]	max [m/min]			
Steel	Non Alloyed	C35, Ck45, 1020, 1045, 1060, 28Mn6	125 HB	0.3	3	0.11	0.23	0.6	180	330	2	0.18	300
			190 HB	0.3	2.5	0.11	0.22	0.52	180	280	2	0.18	260
			250 HB	0.3	2.5	0.11	0.2	0.48	180	250	2	0.18	240
Steel	Low Alloyed	42CrMo4, St50, Ck60, 4140, 4340, 100Cr6	230 HB	0.3	2.5	0.1	0.2	0.48	120	250	2	0.14	240
			280 HB	0.3	2	0.1	0.18	0.4	120	210	2	0.13	200
			180 HB	0.3	2.5	0.1	0.2	0.5	120	280	2	0.14	260
			350 HB	0.3	2	0.1	0.18	0.36	120	180	2	0.13	180
Steel	High Alloyed	X40CrMoV5, H13, M42, D3, S6-5-2, 12Ni19	220 HB	0.3	2.5	0.09	0.18	0.4	70	190	1.7	0.1	180
			280 HB	0.3	2.5	0.09	0.16	0.4	70	150	1.7	0.1	140
			320 HB	0.3	2	0.09	0.14	0.32	70	130	1.7	0.1	120
			350 HB	0.3	2	0.09	0.14	0.26	70	110	1.7	0.1	110
Stainless Steel	Austentic	304, 316, X5CrNi18-9	180 HB	0.3	2.5	0.08	0.18	0.32	170	270	2	0.09	260
			240 HB	0.3	2.5	0.08	0.18	0.26	160	220	2	0.08	210
Stainless Steel	Duplex	X2CrNiN23-4, S31500	290 HB	0.3	2	0.08	0.14	0.2	80	150	1.7	0.08	140
			310 HB	0.3	2	0.08	0.14	0.2	70	140	1.7	0.08	140
Steel	Ferritic & Martensitic	410, X6Cr17, 17-4 PH, 430	200 HB	0.3	2.5	0.08	0.18	0.32	170	250	1.7	0.09	240
			42 HRc	0.3	2	0.08	0.16	0.26	120	190	1.5	0.08	180
Cast Iron	Grey	GG20, GG40, EN-GJL-250, N030B	150 HB	0.3	3	0.08	0.2	0.64	170	250	2	0.18	240
			200 HB	0.3	3	0.08	0.2	0.6	160	230	2	0.18	220
			250 HB	0.3	3	0.08	0.2	0.6	150	210	2	0.18	200
Steel	Malleable & Nodular	GGG40, GGG70, 50005	150 HB	0.3	2.5	0.08	0.18	0.48	120	250	2	0.13	240
			200 HB	0.3	2.5	0.08	0.18	0.4	120	230	2	0.13	220
			250 HB	0.3	2.5	0.08	0.18	0.4	120	190	2	0.13	180
NITI Alloy	Fe, Ni & Co Based	Incoloy 800, Inconel 700, Stellite 21	240 HB	0.3	2	0.09	0.15	0.26	30	50	1.3	0.1	40
			250 HB	0.3	2	0.09	0.15	0.26	30	50	1.3	0.1	40
			350 HB	0.3	2	0.09	0.15	0.26	20	50	1.3	0.1	35
Steel	Ti Based	T40, TiAl6V4	-	0.3	2	0.09	0.14	0.26	40	60	1.3	0.1	50
			-	0.3	2	0.09	0.16	0.32	50	70	1.3	0.14	60
Steel	Hardened Materials	G-X300CrMo15, Ni-Hard 2, X100CrMo13, 440C, G-X260NiCr42	55 HRc	0.3	1.4	0.05	0.09	0.13	30	50	0.9	0.06	40
			400 HB	0.3	1.6	0.05	0.12	0.17	40	60	1.1	0.1	50
			45 HRc	0.3	1.8	0.05	0.12	0.2	50	100	1.4	0.1	90
			50 HRc	0.3	1.5	0.05	0.1	0.17	40	90	1.1	0.08	80
			55 HRc	0.3	1.4	0.05	0.09	0.13	40	80	0.9	0.06	70
Aluminum	Al (>8%Si)	AISi12	130 HB	0.3	4	0.1	0.3	0.7	200	400	2	0.23	350



